

Technical Data Sheet



Product name: Helios Support

Helios Support is a “high heat” water-soluble PVA material which is engineered as support material for dual extrusion 3D printing in combination with engineering materials which require to be printed at higher temperatures and/or in heated build chambers. Helios support can be printed at nozzle temperatures up to 250° C without the risk of cross linking and nozzle clogging and adheres extremely well to styrene based materials such as ABS, TitanX, Crystal Flex, and ApolloX, but also to Python Flex and Volcano PLA.

Helios Support dissolves slightly slower in water than normal PVA, but the dissolving process can be sped up when using warm and circulating water.

Properties	Typical value	Test Method	Test condition
Physical			
Specific gravity	1.19 g/cc	ISO 1183	-
Melt flow rate	58 g/10min	ISO 1133	260° C/5Kg
Water absorption	-	-	-
Moisture absorption	-	-	-
Mechanical			
Impact strength	-	-	-
Tensile strength	-	-	-
Tensile modulus	-	-	-
Elongation at break	-	-	-
Flexural strength	-	-	-
Flexural modulus	-	-	-
Hardness	-	-	-
Thermal			
Print temperature	± 235 - 255° C	-	-
Melting temperature	-	-	-
Viscat softening temp.	-	-	-
Optical			
Haze	-	-	-
Transmittance	-	-	-
Gloss	-	-	-

Product details, certifications and compliance		Diameter	Tolerance	Roundness
HS Code	39169090	1.75mm	± 0.05mm	≥ 95%
REACH compliant	Yes	2.85mm	± 0.10mm	≥ 95%
RoHS certified	Yes			

All information supplied by or on behalf of Formfutura in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by research and, in good faith, believed reliable, but Formfutura assumes no liability and makes no warranties of any kind, express or implied, including, but not limited to, those of title, merchantability, fitness for a particular purpose or non-infringement or any warranty arising from a course of dealing, usage, or trade practice whatsoever in respect of application, processing or use made of the forementioned information or product. The user assumes all responsibility for the use of all information provided and shall verify quality and other properties or any consequence from the use of all such information. Typical values are indicative only and are not to be construed as being binding specifications.